

ORATAPE[®] MT 95

OPTIVIEW Application Tape

Description

Semi-transparent mounting film featuring outstanding dimensional stability and exceptionally high-permanence, even when applied wet.

Adhesive

Modified polyacrylate, medium adhesive power

Recommended Applications

The special composition of the polyacrylate contact adhesive enables problem-free transfer of punched or computer-cut letters and symbols. Even after more than six months of adhesion, a residue-free removal without any considerable increase in adhesive power has been proven. The high tensile strength of the film material ensures precise positioning. This mounting film is suitable for almost all well-known types of glossy or matte-finished films.

Technical Data:

Thickness (paper and adhesive)	6.1 mil
Weight (paper and adhesive)	3.9 oz/yd ²
Elongation at Break (DIN EN ISO 527)	
Along	> 500%
Cross	> 700%
Tensile Strength	
Along	> 25 MPa
Cross	> 25 MPa
Adhesive Power (FINAT TM-1, after 20 min, stainless steel)	~0.5 lb/in ²
Application Temperature	> 50°F
Shelf life (68°F/50% relative humidity in original packaging)	1 year

Attention:

Surfaces to which the material will be applied must be cleaned thoroughly of dust, grease or any contaminants that could affect the adhesion of the material. Freshly painted surfaces should be allowed to stand for at least three weeks after complete curing. The compatibility of selected paints should be tested by the end-user prior to use.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORACAL USA

1100 Oracal Parkway
Black Creek, GA 31308 USA
Toll Free 888.672.2251
912.851.5000 • FAX 912.851.5050
www.oracal.com • ORACAL USA 2008